



**2600 R**



**2750 RJ**



[www.ommelift.dk](http://www.ommelift.dk)

## **CRAWLER MOUNTED BOOM PLATFORM**

**OMMELIFT**



Quality since 1906

OMME LIFT A/S – Lægårdsvej 4 – DK 7260 Sdr. Omme  
Phone: + 45 753 413 00 – Fax: + 45 753 415 92  
E-mail: [omme@ommelift.dk](mailto:omme@ommelift.dk) – Web: [www.ommelift.com](http://www.ommelift.com)

| Technical Data:  | 2600 RB   | 2600 RBD  | 2750 R(B)(D)J |
|--|---|---|---------------|
| Max. working height  | 25.8 m  |   | 27.2 m        |
| Max. platform height                                       | 23.8 m  |   | 25.2 m        |
| Max. outreach  | 12.6 m  |   |               |
| Up and over clearance                                      | -   |   |               |
| Jib length (jib + basket)                                  | -   |   | 2.7 m         |
| Vertical jib rotation                                      | -   |   | 90°           |
| Turret rotation  | ± 355°  |   |               |
| Basket rotation  | ± 41°   |   |               |
| Max. basket load   | 200 kg  |   |               |
| Basket size  | 1.25 x 0.8 x 1.1 m  |   |               |
| Travelling length  | 6.56 / 7.31 m   |   | 6.75 / 7.50 m |
| Travelling height  | 1.99 m  |   |               |
| Travelling width   | 1.10 m  |   |               |
| Operational width  | Wide - Wide<br>Min. 4.59 m – max. 5.32 m  |   |               |
| Stabilizer pad   | 0.28 x 0.44 m   |   |               |
|  | <b>HYBRID</b>   |   |               |
| Diesel engine Kubota D722                                  | 14kW/18.8hp   |   |               |
| Fuel tank capacity   | 23 l  |   |               |
| Generator  | 24 V / 22 A   |   |               |
| Battery pack   | 24V/400Ah/5h  | 24V/200Ah/5h  |               |
| Transformer (240V only)                                    | Standard  | Optional  |               |
| Charger  | 24 V / 30 A   |   |               |
|  | Diesel only version available   |   |               |
|  | See <a href="http://www.ommelift.com">www.ommelift.com</a> for all features and options |   |               |
| Gradeability, max. across slope                            | 25% (14.0°)   |   |               |
| Gradeability, max. up and down slope                       | 35% (19.3°)   |   |               |
| Set-up ability on uneven ground                            | 40% (21.8°)   |   |               |
| Crawler track length                                       | 1.76 m  |   |               |
| Rollers on each side                                       | 4   |   |               |
|  |   |   |               |
| Total weight   | 3625 kg   | 3725 kg   |               |
| Live load in transit position                              | 401 kg/m <sup>2</sup>   | 392 kg/m <sup>2</sup>                                 |               |
| Live load in working position (including max. basket load) | 237 kg/m <sup>2</sup>   | 231 kg/m <sup>2</sup>                                 |               |
| Ground pressure, tracks (Hard surface)                     | 0.51 kg/cm <sup>2</sup><br>(1.80 kg/cm <sup>2</sup> )                                   | 0.53 kg/cm <sup>2</sup><br>(1.90 kg/cm <sup>2</sup> ) |               |
| Ground pressure, outrigger                                 | 1.91 kg/cm <sup>2</sup>   | 1.93 kg/cm <sup>2</sup>                               |               |
| Max. force, outrigger                                      | 23.5 kN   | 23.8 kN   |               |

